Quote Request

☐ Specs Attached ☐ Drawings Attached

Date Quote Rec'd: _____

ThermalRite

10700 Highway 55 ▪ Suite 300 ▪ Plymouth ▪ MN ▪ 55441

Toll Free 888-833-3329 ▪ Fax 763-541-1563

CSR Attn:_____

Date: _____

Job Name: _____

Job Location: _____

Projected Install Date: _____

Company Name: _____ Company Address: _____ Email: _____

Project Contact: _____ _____ Phone: _____

_____ Fax: _____

Single Box ☐ Overall Size of Walk-In Cooler/Freezer:	Indoor	Outdoor	Cooler	Freezer	With Floor	Without Floor	Exterior Finish	Interior Finish	Floor Finish	Ceiling Finish	Pit Depth *(if applies)*
L_____ W_____ H _____ *Item #:*											
Panel Thickness: ☐ 4" ☐ 5" *Item #:*											
Combination Box ☐											
Compartment 1 Size: L_____ W_____ H _____											
Compartment 2 Size: L_____ W_____ H _____											
Compartment 3 Size: L_____ W_____ H _____											

Standard Finish Legend

ACR Acrylume
SA Stucco Aluminum
SW Stucco White
S/S Stainless Steel
GW Galvanized White
PS Patterned Stainless

Other finishes available upon request

Door Detail	Hinge Right	Hinge Left	Interior Protector Plates		Exterior Protector Plates	
			Diam Alum	Stainless	Diam Alum	Stainless
Door Sizes						
A)_____X_____						
B)_____X_____						
C)_____X_____						

Floor Options

1) .050 smooth alum/ply under Load 1,000 lbs
2) 3/16" alum overlay Load 2,500 lbs
3) Super floor Rolling Load 2,000 lbs
4) Super floor w/ overlay Rolling Load 5,000 lbs

Other finishes available upon request

Sketch (Note door locations, bld'g walls, tile thickness & buck opening sizes)

Optional Accessories (check as needed)

___ Pressure Relief Port (Req'd on Freezers)
___ Fluorescent Light(s) 4'
___ LED Lights 4'
___ Locking Bar
___ Internal Ramp ___ External Ramp

___ Heated Observe. Window __14"x14" __14"x24"
___ Unheated Observe. Window __14"x14" __14"x24"
___ Glass Doors ___ Glass Doors by Others
___ Number of Glass Doors (show location on sketch)
___ Bumper Rail (on drawing)
___ Temp. Alarm Installed

___ Third Hinge
___ Trim
___ Roof Cap Flat
___ Sloped Roof

Refrigeration System ___ Outdoor ___ Indoor ___ Pre-Assembled (Remote) ___Quick Connect (Pre-Charged) ___ Length

Compressor Type ___TR Recommendation -- OR -- ___ Hermetic ___ Semi-Hermetic ___ Scroll ___ Discuss ___PRO 3

Temperature Required ___ 35°F ___ 0°F ___-10°F ___ other, please call

Voltage Available ___ 120V (limited units only) ___ 208/230V/60/1 ___208/260V/60/3 480V/60/3

Notes